

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended): A data learning apparatus comprising:

first learning means for deriving a temporary self-organizing map in which classes are associated with respective vector points of reference feature vectors by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and

second learning means for modifying the temporary self-organizing map and deriving a final self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known;

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector on the temporary self-organizing map which has the highest similarity to said one of the second sample feature vectors;

modification means for comparing a class associated with a vector point of the second learning winner vector to a corresponding class of said one of the second sample feature vectors

indicated by the second learning data and, when the class associated with the vector point of the second ~~learning~~ learning winner vector is not identical to the corresponding class indicated by the second learning data, modifying the second learning winner vector and a plurality of reference feature vectors distributed in a second learning vicinity of the second learning winner vector on the temporary self-organizing map so as to reduce the similarity thereof to said one of the second sample feature vectors; and

means for deriving the final self-organizing map by operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors.

2. (original): The data learning apparatus according to claim 1, wherein the modification means further modifies the second learning winner vector and said plurality of reference feature vectors distributed in the second learning vicinity so as to increase the similarity thereof to said one of the second sample feature vectors, when the class associated with the vector point of the second learning winner vector is identical to the corresponding class of said one of the second sample feature vectors indicated by the second learning data.

3. (original): The data learning apparatus according to claim 1, wherein the first learning means includes:

means for generating an initial self-organizing map on which a plurality of random reference feature vectors are distributed;

means for generating a plurality of frequency maps, in which initial values of specified frequency values allocated to respective points are zero, each of the frequency maps corresponding to one class;

first vector specifying means for reading one of first sample feature vectors out of the first learning data and specifying a first learning winner vector on the initial self-organizing map which has the highest similarity to said one of the first sample feature vectors;

update means for modifying the first learning winner vector and a plurality of reference feature vectors distributed in a first learning vicinity of the first learning winner vector on the initial self-organizing map so as to increase the similarity thereof to said one of the first sample feature vectors, and for increasing the specified frequency values in points corresponding to respective vector points of the first learning winner vector and said plurality of reference feature vectors distributed in the first learning vicinity on a frequency map corresponding to a corresponding class of said one of the first sample feature vectors indicated by the first learning data;

means for deriving the temporary self-organizing map by operating each of the first vector specifying means and the update means once or repeatedly more than once for each of said plurality of first sample feature vectors; and

means for defining a class which is most likely to appear at each vector point on the temporary self-organizing map as the class associated with said vector point by referring to said plurality of frequency maps.

4. (original): The data learning apparatus according to claim 1, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a vector having feature quantities indicating features of an image as components thereof, and each of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.

5. (original): A data learning apparatus comprising:

first learning means for deriving a temporary self-organizing map in which classes are associated with respective vector points of reference feature vectors by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and

second learning means for modifying the temporary self-organizing map and deriving a final self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known;

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector having the highest similarity to said one of the second sample feature vectors among the reference feature vectors on the temporary self-organizing map of which the vector points are associated with a class that is identical to a corresponding class of said one of the second sample feature vectors indicated by the second learning data;

modification means for modifying the second learning winner vector and a plurality of reference feature vectors distributed in a second learning vicinity of the second learning winner vector on the temporary self-organizing map so as to increase the similarity thereof to said one of the second sample feature vectors; and

means for deriving the final self-organizing map by operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors.

6. (original): The data learning apparatus according to claim 5, wherein the first learning means includes:

means for generating an initial self-organizing map on which a plurality of random reference feature vectors are distributed;

means for generating a plurality of frequency maps, in which initial values of specified frequency values allocated to respective points are zero, each of the frequency maps corresponding to one class;

first vector specifying means for reading one of first sample feature vectors out of the first learning data and specifying a first learning winner vector on the initial self-organizing map which has the highest similarity to said one of the first sample feature vectors;

update means for modifying the first learning winner vector and a plurality of reference feature vectors distributed in a first learning vicinity of the first learning winner vector on the initial self-organizing map so as to increase the similarity thereof to said one of the first sample feature vectors, and for increasing the specified frequency values in points corresponding to respective vector points of the first learning winner vector and said plurality of reference feature vectors distributed in the first learning vicinity on a frequency map corresponding to a corresponding class of said one of the first sample feature vectors indicated by the first learning data;

means for deriving the temporary self-organizing map by operating each of the first vector specifying means and the update means once or repeatedly more than once for each of said plurality of first sample feature vectors; and

means for defining a class which is most likely to appear at each vector point on the temporary self-organizing map as the class associated with said vector point by referring to said plurality of frequency maps.

7. (original): The data learning apparatus according to claim 5, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a vector having feature quantities indicating features of an image as components thereof, and each of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.

8. (original): A data learning apparatus comprising:

first learning means for deriving a self-organizing map and a plurality of frequency maps, each of which corresponds to one class, by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and

second learning means for modifying said plurality of frequency maps and deciding final classes associated with respective vector points on the self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known;

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector on the self-organizing map which has the highest similarity to said one of the second sample feature vectors;

modification means for performing modification of increasing a specified frequency value of a corresponding point corresponding to a vector point of the second learning winner

vector or specified frequency values of said corresponding point and points distributed in a vicinity thereof on a frequency map corresponding to a correct class which is the same as a corresponding class of said one of the second sample feature vectors indicated by the second learning data among said plurality of frequency maps;

means for operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors; and

means for defining a class which is most likely to appear at each vector point on the self-organizing map as a final class associated with said vector point by referring to said plurality of frequency maps.

9. (original): The data learning apparatus according to claim 8, wherein the modification means performs the modification only in either one of cases where a class associated with a frequency map showing the highest specified frequency value at a point corresponding to a vector point of the second learning winner vector specified by a preceding operation of the second vector specifying means and a corresponding class of said one of the second sample feature vectors indicated by the second learning data are identical and are not identical to each other.



10. (original): The data learning apparatus according to claim 8, wherein the first learning means includes:

means for generating an initial self-organizing map on which a plurality of random reference feature vectors are distributed;

means for generating a plurality of frequency maps, in which initial values of specified frequency values allocated to respective points are zero, each of the frequency maps corresponding to one class;

first vector specifying means for reading one of first sample feature vectors out of the first learning data and specifying a first learning winner vector on the initial self-organizing map which has the highest similarity to said one of the first sample feature vectors;

update means for modifying the first learning winner vector and a plurality of reference feature vectors distributed in a vicinity of the first learning winner vector on the initial self-organizing map so as to increase the similarity thereof to said one of the first sample feature vectors, and for increasing the specified frequency values in points corresponding to respective vector points of the first learning winner vector and said plurality of reference feature vectors distributed in the vicinity on a frequency map corresponding to a corresponding class of said one of the first sample feature vectors indicated by the first learning data; and

means for operating each of the first vector specifying means and the update means once or repeatedly more than once for each of said plurality of first sample feature vectors.

11. (original): The data learning apparatus according to claim 8, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a vector having feature quantities indicating features of an image as components thereof, and each of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.

12. (original): A data learning apparatus comprising:

first learning means for deriving a self-organizing map and a plurality of frequency maps, each of which corresponds to one class, by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and

second learning means for modifying said plurality of frequency maps and deciding final classes associated with respective vector points on the self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known;

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector on the self-organizing map which has the highest similarity to said one of the second sample feature vectors;

modification means for performing modification of decreasing a specified frequency value of a corresponding point corresponding to a vector point of the second learning winner

vector or specified frequency values of said corresponding point and points distributed in a vicinity thereof on some of or all of the frequency maps except for a frequency map corresponding to a correct class which is the same as a corresponding class of said one of the second sample feature vectors indicated by the second learning data among said plurality of frequency maps;

means for operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors; and

means for defining a class which is most likely to appear at each vector point on the self-organizing map to a final class associated with said vector point by referring to said plurality of frequency maps.

13. (original): The data learning apparatus according to claim 12, wherein the modification means further performs modification of increasing a specified frequency value of a corresponding point corresponding to a vector point of the second learning winner vector or specified frequency values of said corresponding point and points distributed in a vicinity thereof on a frequency map corresponding to said correct class.

14. (original): The data learning apparatus according to claim 12, wherein the modification means performs the modification only in either one of cases where a class

associated with a frequency map showing the highest specified frequency value at a point corresponding to a vector point of the second learning winner vector specified by a preceding operation of the second vector specifying means and a corresponding class of said one of the second sample feature vectors indicated by the second learning data are identical and are not identical to each other.

15. (original): The data learning apparatus according to claim 12, wherein the first learning means includes:

means for generating an initial self-organizing map on which a plurality of random reference feature vectors are distributed;

means for generating a plurality of frequency maps, in which initial values of specified frequency values allocated to respective points are zero, each of the frequency maps corresponding to one class;

first vector specifying means for reading one of first sample feature vectors out of the first learning data and specifying a first learning winner vector on the initial self-organizing map which has the highest similarity to said one of the first sample feature vectors;

update means for modifying the first learning winner vector and a plurality of reference feature vectors distributed in a vicinity of the first learning winner vector on the initial self-organizing map so as to increase the similarity thereof to said one of the first sample feature vectors, and for increasing the specified frequency values in points corresponding to respective

vector points of the first learning winner vector and said plurality of reference feature vectors distributed in the vicinity on a frequency map corresponding to a corresponding class of said one of the first sample feature vectors indicated by the first learning data; and

means for operating each of the first vector specifying means and the update means once or repeatedly more than once for each of said plurality of first sample feature vectors.

16. (original): The data learning apparatus according to claim 12, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a vector having feature quantities indicating features of an image as components thereof, and each of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.

17. (cancelled)

18. (cancelled)

19. (original): A data learning program for making a computer operate as:  
first learning means for deriving a temporary self-organizing map in which classes are associated with respective vector points of reference feature vectors by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and

second learning means for modifying the temporary self-organizing map and deriving a final self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known;

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector having the highest similarity to said one of the second sample feature vectors among the reference feature vectors on the temporary self-organizing map of which the vector points are associated with a class that is identical to a corresponding class of said one of the second sample feature vectors indicated by the second learning data;

modification means for modifying the second learning winner vector and a plurality of reference feature vectors distributed in a second learning vicinity of the second learning winner vector on the temporary self-organizing map so as to increase the similarity thereof to said one of the second sample feature vectors; and

means for deriving the final self-organizing map by operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors.

20. (original): The data learning program according to claim 19, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a

vector having feature quantities indicating features of an image as components thereof, and each of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.

21. (original): A data learning program for making a computer operate as:  
first learning means for deriving a self-organizing map and a plurality of frequency maps, each of which corresponds to one class, by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and

second learning means for modifying said plurality of frequency maps and deciding final classes associated with respective vector points on the self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known;

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector on the self-organizing map which has the highest similarity to said one of the second sample feature vectors;

modification means for performing modification of increasing a specified frequency value of a corresponding point corresponding to a vector point of the second learning winner vector or specified frequency values of said corresponding point and points distributed in a vicinity thereof on a frequency map corresponding to a correct class which is the same as a

corresponding class of said one of the second sample feature vectors indicated by the second learning data among said plurality of frequency maps;

means for operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors; and

means for defining a class which is most likely to appear at each vector point on the self-organizing map as a final class associated with said vector point by referring to said plurality of frequency maps.

22. (original): The data learning program according to claim 21, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a vector having feature quantities indicating features of an image as components thereof, and each of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.

23. (original): A data learning program for making a computer operate as:  
first learning means for deriving a self-organizing map and a plurality of frequency maps, each of which corresponds to one class, by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and



second learning means for modifying said plurality of frequency maps and deciding final classes associated with respective vector points on the self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known,

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector on the self-organizing map which has the highest similarity to said one of the second sample feature vectors;

modification means for performing modification of decreasing a specified frequency value of a corresponding point corresponding to a vector point of the second learning winner vector or specified frequency values of said corresponding point and points distributed in a vicinity thereof on some of or all of the frequency maps except for a frequency map corresponding to a correct class which is the same as a corresponding class of said one of the second sample feature vectors indicated by the second learning data among said plurality of frequency maps;

means for operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors; and

means for defining a class which is most likely to appear at each vector point on the self-organizing map to a final class associated with said vector point by referring to said plurality of frequency maps.

24. (original): The data learning program according to claim 23, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a vector having feature quantities indicating features of an image as components thereof, and each of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.

25. (currently amended): A computer-readable recording medium carrying a data learning program for making a computer operate as:

first learning means for deriving a temporary self-organizing map in which classes are associated with respective vector points of reference feature vectors by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and

second learning means for modifying the temporary self-organizing map and deriving a final self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known;

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector on the temporary self-organizing map which has the highest similarity to said one of the second sample feature vectors;

modification means for comparing a class associated with a vector point of the second learning winner vector to a corresponding class of said one of the second sample feature vectors indicated by the second learning data and, when the class associated with the vector point of the second ~~learning~~learning winner vector is not identical to the corresponding class indicated by the second learning data, modifying the second learning winner vector and a plurality of reference feature vectors distributed in a second learning vicinity of the second learning winner vector on the temporary self-organizing map so as to reduce the similarity thereof to said one of the second sample feature vectors; and

means for deriving the final self-organizing map by operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors.

26. (original): The recording medium according to claim 25, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a vector having feature quantities indicating features of an image as components thereof, and each

of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.

27. (original): A computer-readable recording medium carrying a data learning program for making a computer operate as:

first learning means for deriving a temporary self-organizing map in which classes are associated with respective vector points of reference feature vectors by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and

second learning means for modifying the temporary self-organizing map and deriving a final self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known;

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector having the highest similarity to said one of the second sample feature vectors among the reference feature vectors on the temporary self-organizing map of which the vector points are associated with a class that is identical to a corresponding class of said one of the second sample feature vectors indicated by the second learning data;

modification means for modifying the second learning winner vector and a plurality of reference feature vectors distributed in a second learning vicinity of the second learning winner vector on the temporary self-organizing map so as to increase the similarity thereof to said one of the second sample feature vectors; and

means for deriving the final self-organizing map by operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors.

28. (original): The recording medium according to claim 27, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a vector having feature quantities indicating features of an image as components thereof, and each of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.

29. (original): A computer-readable recording medium carrying a data learning program for making a computer operate as:

first learning means for deriving a self-organizing map and a plurality of frequency maps, each of which corresponds to one class, by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and

second learning means for modifying said plurality of frequency maps and deciding final classes associated with respective vector points on the self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known;

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector on the self-organizing map which has the highest similarity to said one of the second sample feature vectors;

modification means for performing modification of increasing a specified frequency value of a corresponding point corresponding to a vector point of the second learning winner vector or specified frequency values of said corresponding point and points distributed in a vicinity thereof on a frequency map corresponding to a correct class which is the same as a corresponding class of said one of the second sample feature vectors indicated by the second learning data among said plurality of frequency maps;

means for operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors; and

means for defining a class which is most likely to appear at each vector point on the self-organizing map as a final class associated with said vector point by referring to said plurality of frequency maps.

30. (original): The recording medium according to claim 29, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a vector having feature quantities indicating features of an image as components thereof, and each of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.

31. (original): A computer-readable recording medium carrying a data learning program for making a computer operate as:

first learning means for deriving a self-organizing map and a plurality of frequency maps, each of which corresponds to one class, by learning first learning data including a plurality of first sample feature vectors for each of which a corresponding class is known; and  
second learning means for modifying said plurality of frequency maps and deciding final classes associated with respective vector points on the self-organizing map by learning second learning data including a plurality of second sample feature vectors for each of which a corresponding class is known,

wherein the second learning means includes:

second vector specifying means for reading one of the second sample feature vectors out of the second learning data and specifying a second learning winner vector on the self-organizing map which has the highest similarity to said one of the second sample feature vectors;

modification means for performing modification of decreasing a specified frequency value of a corresponding point corresponding to a vector point of the second learning winner vector or specified frequency values of said corresponding point and points distributed in a vicinity thereof on some of or all of the frequency maps except for a frequency map corresponding to a correct class which is the same as a corresponding class of said one of the second sample feature vectors indicated by the second learning data among said plurality of frequency maps;

means for operating each of the second vector specifying means and the modification means once or repeatedly more than once for each of said plurality of second sample feature vectors; and

means for defining a class which is most likely to appear at each vector point on the self-organizing map to a final class associated with said vector point by referring to said plurality of frequency maps.

32. (original): The recording medium according to claim 31, wherein each of said plurality of first sample feature vectors and said plurality of second sample feature vectors is a vector having feature quantities indicating features of an image as components thereof, and each of the corresponding classes indicated by the first learning data and the second learning data is a class indicating a meaning of an image.



33. (original): An apparatus for determining meanings of a target image or an image region by use of a self-organizing map obtained after learning, said self-organizing map having meanings of images associated with respective vector points thereon, comprising:

extraction means for extracting one or a plurality of feature vectors from the target image or the image region;

winner vector specifying means for specifying a winner vector on the self-organizing map which has the highest similarity to the feature vector for each of said one or plurality of feature vectors;

meaning determining means for determining the meaning of the target image or the image region based on meanings associated with respective vector points of the winner vectors;

input means for receiving designation of a target image or an image region of which a correct meaning cannot have been determined by the meaning determining means, and input of the correct meaning of said target image or said image region; and

modification means for modifying the self-organizing map by additionally learning the target image or the image region which is designated through the input means,

wherein, for each of one or a plurality of feature vectors extracted from the designated target image or image region, the modification means modifies a winner vector having the highest similarity to the feature vector and a plurality of reference feature vectors distributed in a vicinity of the winner vector on the self-organizing map so as to reduce the similarity thereof to said feature vector.

34. (original): An apparatus for determining meanings of a target image or an image region by use of a self-organizing map obtained after learning, said self-organizing map having meanings of images associated with respective vector points thereon, comprising:

extraction means for extracting one or a plurality of feature vectors from the target image or the image region;

winner vector specifying means for specifying a winner vector on the self-organizing map which has the highest similarity to the feature vector for each of said one or plurality of feature vectors;

meaning determining means for determining the meaning of the target image or the image region based on meanings associated with respective vector points of the winner vectors;

input means for receiving designation of a target image or an image region of which a correct meaning cannot have been determined by the meaning determining means, and input of the correct meaning of said target image or said image region; and

modification means for modifying the self-organizing map by additionally learning the target image or the image region which is designated through the input means,

wherein, for each of one or a plurality of feature vectors extracted from the designated target image or image region, the modification means re-specifies a winner vector having the highest similarity to the feature vector among reference feature vectors on the self-organizing map of which the vector points are associated with a meaning that is identical to the correct meaning, and modifies the re-specified winner vector and a plurality of reference feature vectors

distributed in a vicinity of the re-specified winner vector on the self-organizing map so as to increase the similarity thereof to said feature vector.

35. (original): An apparatus for determining meaning of a target image or an image region by use of a self-organizing map obtained after learning and a plurality of frequency maps each of which corresponds to one meaning of an image, comprising:

extraction means for extracting one or a plurality of feature vectors from the target image or the image region;

vector specifying means for specifying a winner vector on the self-organizing map which has the highest similarity to the feature vector for each of said one or plurality of feature vectors;

meaning determining means for determining the meaning of the target image or the image region based on each meaning associated with a frequency map showing the highest specified frequency value at a point corresponding to each of vector points of the winner vectors;

input means for receiving designation of a target image or an image region of which a correct meaning cannot have been determined by the meaning determining means, and input of the correct meaning of said target image or said image region; and

modification means for modifying said plurality of frequency maps by additionally learning the target image or the image region which is designated through the input means,

wherein, for each of one or a plurality of feature vectors extracted from the designated target image or image region, the modification means increases a specified frequency value of a corresponding point corresponding to a vector point of a winner vector having the highest similarity to said feature vector or specified frequency values of said corresponding point and points distributed in a vicinity thereof on a frequency map corresponding to the correct meaning.

36. (original): An apparatus for determining meaning of a target image or an image region by use of a self-organizing map obtained after learning and a plurality of frequency maps each of which corresponds to one meaning of an image, comprising:

extraction means for extracting one or a plurality of feature vectors from the target image or the image region;

vector specifying means for specifying a winner vector on the self-organizing map which has the highest similarity to the feature vector for each of said one or plurality of feature vectors;

meaning determining means for determining the meaning of the target image or the image region based on each meaning associated with a frequency map showing the highest specified frequency value at a point corresponding to each of vector points of the winner vectors;

input means for receiving designation of a target image or an image region of which a correct meaning cannot have been determined by the meaning determining means, and input of the correct meaning of said target image or said image region; and

modification means for modifying said plurality of frequency maps by additionally learning the target image or the image region which is designated through the input means,

wherein, for each of one or a plurality of feature vectors extracted from the designated target image or image region, the modification means decreases a specified frequency value of a corresponding point corresponding to a vector point of a winner vector having the highest similarity to said feature vector or specified frequency values of said corresponding point and points distributed in a vicinity thereof on some of or all of the frequency maps except for a frequency map corresponding to the correct meaning.

37. (new): The data learning apparatus according to claim 1, wherein the first learning means includes:

means for generating a plurality of frequency maps, in which initial values of specified frequency values allocated to respective points are zero, each of the frequency maps corresponding to one class;

first vector specifying means for reading one of first sample feature vectors out of the first learning data and specifying a first learning winner vector on the initial self-organizing map which has the highest similarity to said one of the first sample feature vectors; and

update means for modifying the first learning winner vector and a plurality of reference feature vectors distributed in a first learning vicinity of the first learning winner vector on the initial self-organizing map so as to increase the similarity thereof to said one of the first sample

feature vectors, and for increasing the specified frequency values in points corresponding to respective vector points of the first learning winner vector and said plurality of reference feature vectors distributed in the first learning vicinity on a frequency map corresponding to a corresponding class of said one of the first sample feature vectors indicated by the first learning data

38. (new): The data learning apparatus according to claim 1, wherein the first learning means includes:

means for defining a class which is most likely to appear at each vector point on the temporary self-organizing map as the class associated with said vector point by referring to a plurality of frequency maps.

39. (new): The data learning apparatus according to claim 4, wherein the meaning of an image corresponds to a descriptor of the contents depicted in an image, and is contained in the feature vectors as a parameter.